3001NV

ALUMINIUM VIDEO ENTRANCE PANEL, 1 BUTTON

Door-entry monitor entrance panel with front plate in 4 mm thick anodised aluminium, buttons with 16 mm diameter, impact-proof grille. Complete with flush-mounted box and anti-intrusion screws. Equipped with a module holder and bulb socket for festoon bulbs (not supplied), diameter 6.3 x 39 mm. The entrance panel should be finished with a door-entry monitor speaker unit depending on the wiring system used. 1 button, 1 wire. Plate dimensions 135x224x4 mm. Box dimensions 115x204x55 mm. 1 bulb socket

3001NV

ALUMINIUM VIDEO ENTRANCE PANEL, 1 BUTTON

GENERAL DATA	
Flush-mounted	Yes

3001NV

ALUMINIUM VIDEO ENTRANCE PANEL, 1 BUTTON

ACCESSORIES

1250IV **ACCESSORY FOR A/V IKALL GROUP ASSEMBLING**

Accessory allowing the installation and use of Ikall audio/video modules part. 4680, 4680C, 4680K, 4680KC, 4681, 4682C, 4682HC, 4682KC, 4682HKC, 4675 and 4673 on single-plate entrance panels. Fitted with a voltage reducer for powering festoon lamps if used with power supply unit 1595 or 1207.

The technical specifications are subject to change without prior notice.